



Mobility Division
 1685 Main Street - Mail Stop 28
 Santa Monica, California 90401
 transportation.planning@santamonica.gov
 PH 310/458-8291

Traffic Control Plan Supplement

Valid only when stamped and signed above

Today's date: _____

The requirement for a Traffic Control Plan (TCP) for (address) _____ has been satisfied subject to the following:

1. The Contractor shall provide and maintain at all times approved delineation including but not limited to signs, arrowboards, barricades, delineators, flaggers and other traffic control devices as may be necessary for the conditions at and near the work site. All signs, arrowboards, barricades, delineators, stripes, markings and other traffic control devices, and the installation thereof, shall comply with the requirements of the latest versions of the following documents:

Traffic Manual, Chapter 5 - "Manual of Traffic Controls for Construction and Maintenance Work Zones" as issued by the State of California, California Department of Transportation, Caltrans

Standard Specifications as issued by the State of California, California Department of Transportation, Caltrans

Work Area Traffic Control Handbook (WATCH Manual) as published by Building News, Inc. (BNI), 3055 Overland Avenue, Los Angeles, California, 90034.

State of California Manual of Traffic Controls (SAF-T Manual) as published by Building News, Inc. (see above for address).

In the event of conflicts between these documents, the most stringent requirement shall apply. Work shall not commence until the traffic control measures are fully in place.

The Contractor shall bear all costs of providing traffic control necessary to ensure safety of the public at and near the work site.

____ 2. Contractor shall maintain one (1) travel lane for traffic in each direction, each lane being a clear minimum distance of 11' (eleven feet) wide on _____.

____ 3. Contractor shall maintain one (1) travel lane for traffic in both directions (reversible lane), the one lane being a clear minimum distance of 11' (eleven feet) wide on _____, with flagger control at each end. Existing traffic lanes shall be free and clear of equipment and obstructions when work is not in progress.

____ 4. Contractor shall provide and maintain at all times sidewalks or passageways safe for pedestrian traffic through and past the work site. Said sidewalks or passageways shall be not less than four-feet (4') in width and shall comply with the requirements of the Americans with Disabilities Act (ADA). In the event the City permits a sidewalk or passageway to be closed to pedestrian use, the requirements set forth in the sheet "Use of Sidewalks" shall be met to provide signing and equipment for safe pedestrian traffic control.

____ 5. Contractor shall comply with the requirements for traffic control in alleys as set forth in the sheet "Use of Alleys".

____ 6. Work shall be permitted during the following checked hours & dates/day of the week or as specified below under "Additional comments":

____ 8:00 a.m. to 6:00 p.m.							
____ 9:00 a.m. to 5:00 p.m.	Date(s): _____	Mon	Tues	Wed	Thurs	Fri	Sat
____ 9:00 a.m. to 3:00 p.m.							

7. Work with Jack Hammers, Pile Drivers, Pavement Breakers or any other equipment producing noise exceeding 900BA is limited to the hours between 10:00 a.m. to 3:00 p.m., except as provided for by Santa Monica Municipal Code Section 4.12.060 Exemptions. Noise is regulated by the Environmental and Public Works Department. Call 310-458-8221 for more information.

8. No work shall be done in the downtown area on Wednesdays or Saturdays, which are Farmer's Market days .

9. In the event steel plates are used to cover an excavation to make the roadway available to traffic, such plates shall be friction surfaced in accordance with the requirements of the Encroachment Permits Manual, "Steel Trench Plating Guidelines", Section 602.1, State of California, Department of Transportation, Caltrans. The plates shall be tapered smooth to the pavement at the edges with an asphalt cold mix. Plates must be sufficiently strong to support all vehicular traffic. Smooth plates shall NOT be used. If plates are used, proper warning signs (W33, Rough Road, with black lettering on an orange background) or other approved signs shall be placed on the approaches to the plated area.

10. Addition comments _____