



NOTES:

MINIMUM 24" RECOMPACTED SUBGRADE
COMPACTED TO 90% RC.

① ASPHALT SECTION - 8" AC/6" BASE

1. ASPHALT: HOT-MIX: DENSE, HOT-LAID, HOT-MIX ASPHALT PLANT MIX III-C3 PG 64-10 IN CONFORMANCE WITH SSPWC SECTION 400-4.
2. BASE COURSE: CRUSHED MISC. BASE COMPACTED TO 95% RC.

② CONCRETE SECTION - 4" CONCRETE

1. CONCRETE: CLASS 660-C-4000
2. SAWCUT JOINTS 1-1/2" DEEP, 1/4" WIDE:
 - A. CROSS WISE AT 5' INTERVALS, AND
 - B. LONGITUDINALLY IN THE CENTER OR AT 5' INTERVALS, WHICHEVER SPACING IS LESS.

* BIKEWAY CAN BE CONSTRUCTED OF ASPHALT OR CONCRETE, DEPENDING ON MATERIALS USED FOR THE ABUTING SURFACES.

** HEADERS TO BE USED WHEREVER ASPHALT DOES NOT ADJOIN OTHER PAVING; ALTERNATIVE MATERIAL TO REDWOOD MAY BE USED IF APPROVED BY THE CITY ENGINEER.



City of Santa Monica
Department of Public Works

1437 4th Street, Suite 300 Santa Monica, CA 90401
TEL. (310) 458-8721 FAX. (310) 393-4425
e-mail : smengineering@smgov.net

SANTA MONICA BIKEWAY
COMBINED CLASS I BIKE/PEDESTRIAN
PATH ADJACENT TO STREET

SUBMITTED BY :

APPROVED BY :

[Signature]
[Signature]
City Engineer

DATE : 8-5-2012

DRAWING NO.

B-5

5 of 5