


TYPICAL SECTION
N.T.S.



NOTES

1. PERVIOUS CONCRETE GUTTERS SHALL ONLY BE CONSTRUCTED WHERE LONGITUDINAL ALLEY GRADE IS LESS THAN OR EQUAL TO 20%.
2. WHERE UNDERGROUND UTILITIES CONFLICT, INFILTRATION GALLERY MAY BE ELIMINATED.
3. GEO FABRIC SHALL BE CHRISTY'S NONWOVEN GEOTEXTILE 12' WIDE #TC-DF 144360-4 OR EQUAL. APPLY MIN. 2' OVERLAP AT ALL JOINTS AND ENDS.
4. SUBGRADE SHALL BE COMPACTED TO MINIMUM DENSITY OF 90% PER ASTM D1557.



City of Santa Monica
Department of Public Works
1437 4th St. Suite 300, Santa Monica, Ca. 90401
TEL. (310) 458-8721 FAX. (310) 393-4425
smengineering@smgov.net

**STANDARD DETAIL FOR
PERVIOUS CONCRETE ALLEY GUTTER**

SUBMITTED BY: RICK VALTE, P.E. 	DRAWING NO. SM18
APPROVED BY:  CITY ENGINEER	DATE: 2-28-2012

1 OF 1